

## KHUMBU



**4443**  
KHUMBU  
↔ 11 cm  
↔ 11 cm  
1 x G9, max 40W  
IP 44

IP 44



**4903**  
DESNA  
↓ 11 cm  
↔ 11 cm  
1 x G9, max 40W  
IP 44

## DESNA

## SEMI



**6775**  
SEMI  
↔ 11,5 cm  
↔ 2,8 cm  
36 x 0,2W LED CREE  
3000K, 242lm  
IP 54

## ZEM

## PEAK

## DRAS

IP 54

## MUNO



**4444**  
ZEM  
↔ 10 cm  
↔ 5 cm  
4 x 1W LED CREE  
IP 54



**4441**  
PEAK  
↓ 17 cm  
↔ 6,5 cm  
2 x 3W LED CREE  
IP 54



**4442**  
DRAS  
↓ 12,5 cm  
↔ 9 cm  
2 x 3W LED CREE  
IP 54



**6776**  
MUNO  
↔ 22 cm  
↔ 13 cm  
1 x 6W LED CREE  
3000K, 242lm  
IP 54



Item No.	Watt	Colour temperature (Kelvin)	Luminous flux	Beam Angle	Colour Rendering Index (CRI ≥)	Input	Power factor	Safety type
4441	2 x 3W LED CREE	3000K	62lm	83°	80	⊕ ~200-240V, 50Hz	0,91	IP54 ⚡ ⚠
4442	2 x 3W LED CREE	3000K	122lm	65°	78	⊕ ~200-240V, 50Hz	0,91	IP54 ⚡ ⚠
4444	4 x 1W LED CREE	3000K	321lm	16°	80	⊕ ~200-240V, 50Hz	0,89	IP54 ⚡ ⚠

Item No.	Watt	Colour temperature (Kelvin)	Luminous flux	Beam Angle	Colour Rendering Index (CRI ≥)	Input	Power factor	Safety type
6775	36 x 0,2W LED CREE	3000K	242lm	120°	80	⊕ ~200-240V, 50Hz	0,54	IP54 ⚡ ⚠
6776	1 x 6W LED CREE	3000K	242lm	120°	80	⊕ ~200-240V, 50Hz	0,54	IP54 ⚡ ⚠