

BRICK




3408
BRICK
↔ 22 cm
↔ 12 cm
1 x E27, max 60W
IP 65

BASALT



3412
BASALT
↓ 12,5 cm
↔ 22,5 cm
1 x E14, max 60W
IP 44

4966
srebrny
серебряный
silver



aluminium, PC | aluminium, PC | алюминий, PC

ORINOKO

IP 44




4387
ORINOKO
↔ 29 cm
↔ 13 cm
1 x E27, max 20W
IP 44

aluminium, PC | aluminium, PC | алюминий, PC

ASSAM




4453
ASSAM
↔ 23 cm
↔ 8 cm
1 x E27, max 18W
IP 65



IP 65



4907
INA
↔ 23 cm
↔ 8 cm
1 x E27, max 18W
IP 65




aluminium, szkło | aluminium, glass | алюминий, стекло




PERI

4452
PERI
↔ 13 cm
↔ 8 cm
1 x 3W LED CREE
IP 65



RIMO


4450
RIMO
↔ 11,5 cm
↔ 6,5 cm
2 x 1W LED CREE
IP 65



SHIRE

IP 65

5488
SHIRE GRAPHITE
↓ 17,1 cm
↔ 7,3 cm
1 x 3W LED CREE
IP 65



STEP

NEW!

6908
STEP LED WHITE
↓ 7 cm
↔ 6,5 cm
1 x 3W LED
IP 44



6907
STEP LED GRAPHITE
↓ 7 cm
↔ 6,5 cm
1 x 3W LED
IP 44



aluminium | aluminium | алюминий

Item No.	Watt	Colour temperature (Kelvin)	Luminous flux	Beam Angle	Colour Rendering Index (CRI ≥)	Input	Power factor	Safety type
4452	1 x 3W LED CREE	3000K	61lm	84°	77	Ⓢ~200-240V, 50Hz	0,45	IP65 ⚡ ⚠ ⚠
4450	2 x 1W LED CREE	3000K	169lm	29°	80	Ⓢ~200-240V, 50Hz	0,43	IP65 ⚡ ⚠ ⚠
5488	1 x 3W LED CREE	3000K	59lm	23°	83	Ⓢ~200-240V, 50Hz	0,52	IP65 ⚡ ⚠ ⚠
6908	1 x 3W LED EPISTAR	3000K	310lm	92°	80	Ⓢ~220-240V, 50Hz	0,57	IP44 ⚡
6907	1 x 3W LED EPISTAR	3000K	310lm	92°	80	Ⓢ~220-240V, 50Hz	0,57	IP44 ⚡

aluminium, szkło | aluminium, glass | алюминий, стекло